

> E1C/4



TIPO - TYPE	50 Hz - 1500 giri/1' - cosφ = 1						60 Hz - 1800 giri/1' - cosφ = 1					
	Potenza resa Rating kVA (kW)	Rendimento % Efficiency %		Potenza assorbita Driving power		Potenza resa Rating kVA (kW)	Rendimento % Efficiency %		Potenza assorbita Driving power			
		4/4	3/4	kW	HP		4/4	3/4	kW	HP		
E1C13S A/4	5.5	77.0	78.0	7.1	9.5	7	78.0	78.5	9.0	12.1		
E1C13S B/4	7	78.0	79.0	9.0	12.0	8.5	79.0	80.0	10.8	14.5		
E1C13S C/4	8	79.0	80.0	10.1	13.5	9.75	80.0	80.5	12.2	16.4		
E1C13S D/4	9	79.5	80.0	11.3	15.2	11	80.0	81.0	13.8	18.5		
E1C13M E/4	11.5	80.0	81.0	14.4	19.3	14	81.0	81.5	17.3	23.2		
E1C13M F/4	12.5	81.5	82.0	15.3	20.5	15	81.5	82.5	18.4	24.7		

TIPO - TYPE	Potenza resa - Rating (kVA)		Mom. di inerzia Mom. of inertia (J) (kgm2)		Peso - Weight (kg)			Volume aria Air volume (m3/1')	
	50 Hz	60 Hz	B3/B14	B2 SAE	B3/B9	B3/B14	B2	50 Hz	60Hz
	E1C13S A/4	5.5	7	0.044	0.048	44.0	47.0	51.1	5.4
E1C13S B/4	7	8.5	0.049	0.054	50.6	53.5	57.6	5.3	6.4
E1C13S C/4	8	9.75	0.055	0.061	57.1	60.0	64.1	5.1	6.1
E1C13S D/4	9	11	0.060	0.066	61.5	64.4	68.5	4.9	5.9
E1C13M E/4	11.5	14	0.072	0.079	76.6	79.5	83.6	4.7	5.6
E1C13M F/4	12.5	15	0.075	0.083	80.1	83.0	87.1	4.6	5.5